

INCOMPATIBILITY (MATERIALS TO AVOID): No information

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon monoxide, carbon dioxide, oxides of nitrogen, and possibly acrolein.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Vapor or mist may cause headache, nausea or irritation of the nose, throat and lungs. Observe any TWA limits on the hazardous ingredients in Section II of this MSDS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

N.A.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

May be harmful if absorbed through the skin. May cause an allergic reaction

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

May cause pain or discomfort in the mouth, chest or abdomen. Gastrointestinal irritation, vomiting, nausea, diarrhea, dizziness, drowsiness, faintness, weakness or collapse may also occur under extreme circumstances.

HEALTH HAZARDS (ACUTE AND CHRONIC): Acute.

CARCINOGENICITY: NTP CARCINOGEN:

IARC MONOGRAPHS: Not available

OSHA REGULATED: Not available

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Respiratory tract infection, dermatitis, nausea

EMERGENCY AND FIRST AID PROCEDURES:

EYE EXPOSURE:

N.A.

SKIN EXPOSURE:

N.A. INHALATION:

N.A. INGESTION:

N.A.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate ignition sources, provide good ventilation, dike spill area and add absorbent earth or sawdust to spilled liquid.

WASTE DISPOSAL METHOD:

Collect absorbent/water/spilled liquid mixture into metal containers. Consult local, state & federal hazardous waste regulations before disposing into approved hazardous waste landfills. Obey all local, county, state and federal laws.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Use in well-ventilated areas. Store in areas approved for flammable materials. Keep containers closed when not in use. Tools used with this material should be made of aluminum, brass or copper. Protect from freezing and prevent contact with excessive heat.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION:

When handling this material, use a NIOSH approved cartridge respirator suitable to keep airborne mists and vapor concentrations below the time weighted threshold limits. If using in a poorly ventiated or confined area, use a fresh-air supplying respirator or self-contained breathing apparatus.

VENTILATION:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV. Ventilation equipment should be explosion proof.

PROTECTIVE GLOVES:

Use impermeable chemical handling gloves for skin protection

EYE PROTECTION:

Use chemical safety glasses, goggles, and faceshields for eye protection.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

An eye wash station and/or safety shower should be accessible. Impermeable aprons and head caps are recommended when handling this material.

WORK/HYGIENIC PRACTICES:

Wash thoroughly after use and before eating, drinking or using tobacco products.

===== SECTION IX - REGULATORY INFORMATION =====

N.A.

===== SECTION X - DISCLAIMER =====

To the best of our knowledge, this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State and Local laws and regulations. No guarantee or warranty is expressed or implied based on the information contained herein.